

Good to know: Passive error flags

When the error flag is sent, the other nodes might not detect this passive error flag at all, because they cannot distinguish between bus-idle (recessive state) and the error frame made entirely by recessive bits.

This is a critical situation from the viewpoint of the network system. Data consistency is not more provided. Therefore,


Error passive frames comprise the 6-bit error flag (all recessive), the 1-bit to 6-bit overlapping error flag caused by other nodes, and the 8-bit recessive error delimiter. The ISO 11898-1:2015 standard reads “the passive error flag is complete when these 6 equal bits have been detected”. What does this mean? It means, when a receiving node in error passive mode, which has signaled an error, is detecting 6 consecutive recessive bits (length of the passive error flags) on the bus, it completes its passive error flag. Now, this node is allowed to transmit CAN frames again.

If there is heavy traffic, on the bus by other nodes, it can take a while, until the passive error flag is completed. In this time, the node is not able to transmit other data frames.

the application layer should take care on this scenario. In CANopen, the Emcy message is used to indicate to the other nodes, that the CAN interface of this CANopen device is in error passive state and cannot indicate a corrupted data frame received from another node. But you can do more: The CANopen device can already transmit an Emcy message, when it reaches the error warning level (by default 96 for TEC and REC). Therefore, CiA recommends supporting the related 8120_h error code in Emcy messages. Reaching the error warning level, can also be indicated in the EMCY message in the manufacturer-specific field.

hz

www.can-newsletter.org



Sontheim


Your reliable partner for innovative CAN systems

From design over implementation to testing

- ▶ Mobile or stationary CAN Interfaces in various form factors with WLAN, Bluetooth, Ethernet, USB and more
- ▶ Robust CAN Gateways and Data Logger with up to 256GB of built-in NAND-Flash-Memory
- ▶ Rugged ECUs for controlling, telemetry services and diagnostic application
- ▶ Monitoring and analyzing - our modular software tools for efficient fieldbus diagnostics
- ▶ Searching for a modular diagnostic tool based on standards? Have a look on our MDT!
<http://www.sontheim-industrie-elektronik.de/en/products/automotive/diagnostics-tools/>



Sontheim Overview and Portfolio:



We live electronics!
www.sontheim-industrie-elektronik.de

DE Sontheim Industrie Elektronik GmbH
Georg-Krug-Str. 2, 87437 Kempten
Tel: +49 831 57 59 00-0 - Fax: -73
info@s-i-e.de

US Sontheim Industrial Electronics Inc.
One West Court Square, Suite 750
Decatur, GA 30030
Phone: +1 (563) 888-1471



CAN in Automation

The non-profit CiA organization promotes CAN and CAN FD, develops CAN FD recommendations and CANopen specifications, and supports other CAN-based higher-layer protocols.

Join the community!

- ▶ Initiate and influence CiA specifications
- ▶ Receive information on new CAN technology and market trends
- ▶ Have access to all CiA technical documents also in work draft status
- ▶ Participate in joint marketing activities
- ▶ Exchange knowledge and experience with other CiA members
- ▶ Get the CANopen vendor-ID free-of-charge
- ▶ Get credits on CANopen product certifications
- ▶ Get credits on CiA training and education events
- ▶ Benefit from social networking with other CiA members
- ▶ Get credits on advertisements in CiA publications

*For more details please contact CiA office
at headquarters@can-cia.org*

www.can-cia.org